

Pump Type	kW	Q	m³/h	0	123	246	366	489	612	735	855	978	1101
			l/sec	0	34.2	68.3	101.7	135.8	170.0	204.2	237.5	271.7	305.8
			l/min	0	2050	4100	6100	8150	10200	12250	14250	16300	18350

Pump Type	kW	H (m) — P1 (kW)	H: total manometer head. P1: power absorbed from the pump.																
			H	P1	H	P1	H	P1	H	P1	H	P1	H	P1					
PZ2210/35/1L	37		20.7	15.9	20.0	19.5	19.5	23.0	18.8	26.4	17.7	29.6	15.9	32.6	13.1	35.3	--	--	--
PZ2210/40/1F	55		24.3	21.5	23.6	23.0	29.8	22.4	33.7	21.6	37.6	20.3	41.3	18.3	44.7	15.5	47.7	--	--
PZ2210/40/1C	75		27.0	26.3	26.2	25.7	35.3	25.1	39.7	24.4	44.0	23.3	48.2	21.7	52.1	19.5	55.6	16.3	58.9
PZ2210/40/1	75		28.7	29.7	27.9	27.4	39.4	26.8	44.0	26.2	48.6	25.2	53.1	23.8	57.4	21.9	61.3	19.1	64.9
PZ2210/40/2L	75		41.4	31.8	40.0	39.0	46.0	37.7	52.7	35.5	59.3	31.8	65.3	26.1	70.7	--	--	--	--
PZ2210/45/2F	110		48.6	43.1	47.1	46.0	59.5	44.9	67.4	43.2	75.2	40.6	82.5	36.6	89.4	31.0	95.4	--	--
PZ2210/50/2C	132		53.9	52.5	52.4	51.3	70.6	50.2	79.3	48.8	88.0	46.7	96.3	43.5	104.1	39.0	111.2	32.7	117.8
PZ2212/60/2	160		57.3	59.4	55.9	54.7	78.7	53.7	88.0	52.3	97.3	50.4	106.2	47.6	114.7	43.7	122.5	38.2	129.8
PZ2210/50/3H	132		65.8	53.2	63.7	62.1	75.7	60.2	86.4	57.3	96.8	52.4	106.5	44.9	115.4	--	--	--	--
PZ2212/60/3F	160		72.9	64.6	70.7	69.1	89.3	67.3	101.1	64.8	112.8	60.9	123.8	54.9	134.0	46.5	143.1	--	--
PZ2212/60/3C	200		80.9	78.8	78.6	77.0	106.0	75.4	119.0	73.2	132.0	70.0	144.5	65.2	156.2	58.5	166.8	49.0	176.7
PZ2212/60/3	250		86.0	89.1	83.8	82.1	118.1	80.5	132.0	78.5	145.9	75.6	159.3	71.4	172.1	65.6	183.8	57.4	194.8
PZ2212/60/4F	200		97.2	86.1	94.3	92.1	119.1	89.8	134.8	86.5	150.4	81.2	165.1	73.2	178.7	61.9	190.8	--	--
PZ2212/60/4C	250		107.8	105.0	104.9	102.6	141.3	100.5	158.7	97.6	176.0	93.3	192.6	86.9	208.3	78.0	222.4	65.4	235.6
PZ2212/60/4	280		114.7	118.8	111.7	109.4	157.4	107.3	176.0	104.7	194.5	100.8	212.4	95.2	229.5	87.4	245.0	76.5	259.7
PZ2212/60/5E	280		126.8	116.8	123.1	120.3	159.7	117.6	180.2	113.7	200.5	107.7	219.8	98.6	237.9	85.7	254.0	--	--
PZ2212/60/5C	315		134.8	131.3	131.1	128.3	176.6	125.6	198.3	122.0	220.0	116.7	240.8	108.7	260.3	97.5	278.0	81.7	294.5
PZ2212/70/5	355		143.4	148.5	139.6	136.8	196.8	134.2	220.0	130.8	243.2	126.0	265.5	119.0	286.8	109.3	306.3	95.6	324.6

## — ACCESSORIES FEATURES —

Motor power kW	Motor Size	Axis line	Drive unit	Base	Flange discharge	Foot valve	Strainer
30	225	LA 10/30	ME250.6/30	PZ 250	DN 250 - PN 25	—	SU12"
37	250	LA 10/35	ME250.7/35				
45	280	LA 10/40	ME250.7/40				
55			ME250.8/40				
75			ME250.8/45				
90 - 110	315	LA 10/45	ME250.8/50				
132		LA 10/50	ME250.8/50				
160 - 200 - 250 - 280	355	LA 12/60	ME300.9/60	PZ 300	DN 300 - PN 25	—	—
315	400	LA 12/70	ME300.10/60				
355		ME300.10/70					

22 INCH

